

GEA Mission The Global Electronics Association promotes industry growth and strengthens supply chain resilience.

About IPC Standards by Global Electronics Association

IPC standards and publications by Global Electronics Association are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for their particular need. Existence of such standards and publications shall not in any respect preclude any entity from manufacturing or selling products not conforming to such standards and publications, nor shall the existence of such standards and publications preclude their voluntary use.

IPC standards and publications by Global Electronics Association are approved by committees without regard to whether the standards or publications may involve patents on articles, materials or processes. By such action, Global Electronics Association does not assume any liability to any patent owner, nor does Global Electronics Association assume any obligation whatsoever to parties adopting a standard or publication. Users are wholly responsible for protecting themselves against all claims of liabilities for patent infringement.

Global Electronics Association Position Statement on Specification Revision Change

The use and implementation of IPC standards and publications by Global Electronics Association are voluntary and part of a relationship entered into by customer and supplier. When a standard or publication is revised or amended, the use of the latest revision or amendment as part of an existing relationship is not automatic unless required by the contract. Global Electronics Association recommends the use of the latest revision or amendment.

Standards Improvement Recommendations

Global Electronics Association welcomes comments for improvements to any standard in its library. All comments will be provided to the appropriate committee.

If a change to technical content is requested, data to support the request is recommended. Technical comments to include new technologies or make changes to published requirements should be accompanied by technical data to support the request. This information will be used by the committee to resolve the comment.

To submit your comments, visit the Status of Standardization page at www.electronics.org/status.

Global Electronics Association Staff Recommends:	IPC-D-620 Design and Critical Process Requirements for Cable and Wiring Harnesses
	IPC-HDBK-620 Handbook and Guide to IPC-D-620 and IPC/WHMA-A-620



IPC/WHMA-A-620F

Requirements and Acceptance for Cable and Wire Harness Assemblies

If a conflict occurs
between the English
language and translated
versions of this document,
the English version will
take precedence.

Developed by the IPC/WHMA-A-620 Task Group (7-31f) of the Product Assurance Committee (7-30) of Global Electronics Association

Global Electronics Association Standards and Artificial Intelligence (AI) Statement

Global Electronics Association is the trading name of IPC International, Inc., which owns the copyright to all IPC Standards and other IPC materials.

The Global Electronics Association explicitly prohibits:

- The integration or transfer of any data whether in the form of IPC books, standards, metadata, or other formats — into AI engines or algorithms by any person or entity, including authorized distributors and their end users.
- Activities involving data harvesting, text and data mining, enrichment, or the creation of derivative works based on this data, including the use of automated data collection methods or artificial intelligence.

Any breach of these provisions is considered a copyright infringement unless expressly authorized in advance in writing by the Global Electronics Association.

Supersedes:

IPC/WHMA-A-620E – October 2022
IPC/WHMA-A-620D – January 2020
IPC/WHMA-A-620C – January 2017
IPC/WHMA-A-620B with
Amendment 1 – August 2013
IPC/WHMA-A-620B – October 2012
IPC/WHMA-A-620A – July 2006
IPC/WHMA-A-620 – January 2002

Users of this publication are encouraged to participate in the development of future revisions.

Contact:

Global Electronics Association
3000 Lakeside Drive, Suite 105N
Bannockburn, Illinois
60015-1249
Tel 847 615.7100
Fax 847 615.7105

Table of Contents

1.0	GENERAL	1-1	1.12.2	Visual Inspection	1-5
1.1	Scope	1-1	1.12.2.1	Lighting.....	1-5
1.2	Purpose	1-1	1.12.2.2	Magnification Aids	1-5
1.3	Classification	1-1	1.13	Facilities	1-6
1.4	Measurement Units and Applications	1-1	1.13.1	Field Assembly Operations.....	1-6
1.4.1	Verification of Dimensions	1-1	1.13.2	Health and Safety	1-6
1.4.2	Relationship of AWG and Wire Size.....	1-1	1.14	Electrostatic Discharge (ESD) Protection	1-6
1.5	Definition of Requirements	1-1	1.15	Tools and Equipment	1-6
1.5.1	Inspection Conditions.....	1-2	1.15.1	Control.....	1-6
1.5.1.1	Acceptable	1-2	1.15.2	Calibration	1-6
1.5.1.2	Defect.....	1-2	1.16	Materials and Processes	1-7
1.5.1.2.1	Disposition	1-2	1.17	Electrical Clearance	1-7
1.5.1.3	Process Indicator	1-2	1.18	Contamination	1-7
1.5.1.4	Conditions Not Specified.....	1-2	1.19	Rework/Repair	1-7
1.5.1.5	Uncommon or Specialized Designs.....	1-3	1.19.1	Rework.....	1-7
1.5.2	Material and Process Nonconformance	1-3	1.19.2	Repair.....	1-7
1.6	Process Control	1-3	1.19.3	Post Rework/Repair Cleaning	1-7
1.6.1	Statistical Process Control	1-3	2.0	APPLICABLE DOCUMENTS	2-1
1.7	Order of Precedence	1-4	2.1	IPC	2-1
1.7.1	Clause References	1-4	2.2	Joint Industry Standards	2-1
1.7.2	Appendices.....	1-4	2.3	Society of Automotive Engineers (SAE)	2-1
1.8	Terms and Definitions	1-4	2.4	International Organization for Standardization (ISO)	2-2
1.8.1	FOD (Foreign Object Debris)	1-4	2.5	ESD Association (ESDA)	2-2
1.8.2	Inspection	1-4	2.6	United States Department of Defense (DoD)	2-2
1.8.3	Manufacturer (Assembler)	1-4	2.7	International Electrotechnical Commission (IEC)	2-2
1.8.4	Objective Evidence	1-4	2.8	Aerospace Industries Association (AIA/NAS)	2-2
1.8.5	Process Control.....	1-4	2.9	Electronics Industries Alliance	2-2
1.8.6	Supplier	1-4	2.10	ASTM International	2-2
1.8.7	User.....	1-4	3.0	WIRES	3-1
1.8.8	Diameter	1-4	3.1	Stripping	3-1
1.8.8.1	Conductor Diameter	1-4	3.2	Strand Damage and End Cuts	3-1
1.8.8.2	Wire Diameter.....	1-4	3.3	Conductor Deformation/Birdcaging	3-3
1.8.8.3	Strand Diameter	1-4	3.4	Twisting of Wires	3-4
1.8.9	Engineering Documentation.....	1-4	3.5	Insulation Damage – Stripping	3-5
1.9	Requirements Flowdown	1-5	4.0	SOLDERED TERMINATIONS	4-1
1.10	Personnel Proficiency	1-5	4.1	Materials and Components	4-1
1.11	Acceptance Requirements	1-5	4.1.1	Materials	4-1
1.12	Inspection Methodology	1-5			
1.12.1	Process Verification Inspection.....	1-5			

Table of Contents (cont.)

4.1.1.1	Solder	4-1	4.8.5.1	Lead/Conductor(s) Placement	4-33
4.1.1.1.1	Solder Purity Maintenance	4-2	4.8.5.2	Solder	4-34
4.1.1.2	Flux	4-3	4.8.6	Cup	4-35
4.1.1.3	Adhesives	4-3	4.8.6.1	Lead/Conductor(s) Placement	4-35
4.1.1.4	Solderability	4-3	4.8.6.2	Solder	4-36
4.1.2	Gold Removal	4-3	4.8.7	Series Connected	4-38
4.2	Cleanliness	4-4	4.8.8	AWG 30 and Smaller Diameter Wires	4-39
4.2.1	Presoldering	4-4	5.0	CRIMP TERMINATIONS (CONTACTS AND LUGS)	5-1
4.2.2	Postsoldering	4-4	5.1	Stamped and Formed – Open Barrel	5-3
4.2.2.1	Foreign Object Debris (FOD)	4-4	5.1.1	Insulation Support	5-4
4.2.2.2	Flux Residue	4-5	5.1.1.1	Inspection Window	5-4
4.2.2.2.1	Cleaning Required	4-5	5.1.1.2	Crimp	5-5
4.2.2.2.2	No-Clean Process	4-5	5.1.2	Insulation Clearance if No Support Crimp	5-7
4.3	Solder Connection	4-6	5.1.3	Conductor Crimp	5-7
4.3.1	General Requirements	4-7	5.1.4	Crimp Bellmouth	5-9
4.3.2	Soldering Anomalies	4-8	5.1.5	Conductor Brush	5-10
4.3.2.1	Partially Visible or Hidden Solder Connections	4-8	5.1.6	Carrier Cutoff Tab	5-12
4.4	Wire/Lead Preparation, Tinning	4-9	5.1.7	Individual Wire Seal	5-13
4.5	Wire Insulation	4-11	5.2	Stamped and Formed – Closed Barrel	5-15
4.5.1	Clearance	4-11	5.2.1	Insulation Clearance	5-16
4.5.2	Postsolder Damage	4-13	5.2.2	Insulation Support Crimp	5-17
4.6	Insulation Sleeveing	4-14	5.2.3	Conductor Crimp and Bellmouth	5-18
4.7	Soldered Strand Separation (Birdcaging)	4-16	5.2.4	Cutoff Tabs	5-20
4.8	Terminals	4-17	5.3	Machined Contacts	5-21
4.8.1	Turrets and Straight Pins	4-20	5.3.1	Insulation Clearance	5-21
4.8.1.1	Lead/Conductor(s) Placement	4-20	5.3.2	Insulation Support Style	5-23
4.8.1.2	Solder	4-22	5.3.3	Conductor	5-24
4.8.2	Bifurcated	4-23	5.3.4	Crimping	5-26
4.8.2.1	Side Route	4-23	5.3.5	CMA Buildup	5-28
4.8.2.2	Bottom and Top Route	4-25	5.4	Termination Ferrule Crimp	5-30
4.8.2.3	Staked/Constrained Wires	4-26	5.5	Crimped Terminals	5-32
4.8.2.4	Solder	4-27	6.0	INSULATION DISPLACEMENT CONNECTION (IDC)	6-1
4.8.3	Slotted	4-29	6.1	Mass Termination, Flat Cable	6-1
4.8.3.1	Lead/Conductor(s) Placement	4-29	6.1.1	End Cutting	6-1
4.8.3.2	Solder	4-30	6.1.2	Notching	6-2
4.8.4	Pierced/Perforated/Punched	4-31	6.1.3	Planar Ground Plane Removal	6-3
4.8.4.1	Lead/Conductor(s) Placement	4-31	6.1.4	Connector Position	6-4
4.8.4.2	Solder	4-32	6.1.5	Connector Skew and Lateral Position	6-6
4.8.5	Hook	4-33			

Table of Contents (cont.)

6.1.6	Retention	6-7	9.2.2	Wire Dress	9-7
6.2	Discrete Wire Termination	6-8	9.2.2.1	Straight Approach	9-7
6.2.1	General.....	6-8	9.2.2.2	Side Approach.....	9-8
6.2.2	Position of Wire	6-9	9.3	Sleeving and Boots	9-9
6.2.3	Overhang (Extension).....	6-9	9.3.1	Position	9-9
6.2.4	Insulation Crimp.....	6-11	9.3.2	Bonding.....	9-10
6.2.5	Damage in Connection Area	6-12	9.4	Connector Damage	9-12
6.2.6	End Connectors.....	6-13	9.4.1	Criteria.....	9-12
6.2.7	Pass Through Connectors	6-14	9.4.2	Limits – Hard Face – Mating Surface.....	9-13
6.2.8	Wiremount Connectors	6-15	9.4.3	Limits – Soft Face – Mating Surface or Rear Seal Area	9-14
6.2.9	Subminiature D-Connector (Series Bus Connector)	6-16	9.4.4	Contacts.....	9-15
6.2.10	Modular Connectors (RJ Type).....	6-18	9.4.4.1	Exposed Sockets, Protected Pins	9-16
7.0	ULTRASONIC WELDING	7-1	9.5	Installation of Contacts and Sealing Plugs into Connectors	9-16
7.1	Insulation Clearance	7-1	9.5.1	Installation of Contacts	9-17
7.2	Weld Nugget	7-2	9.5.2	Installation of Sealing Plugs.....	9-18
8.0	SPLICES	8-1	10.0	OVER-MOLDING/POTTING	10-1
8.1	Soldered Splices	8-1	10.1	Over-Molding	10-1
8.1.1	Mesh	8-2	10.1.1	Mold Fill	10-1
8.1.2	Wrap	8-2	10.1.1.1	Inner	10-1
8.1.3	Hook	8-3	10.1.1.2	Outer.....	10-4
8.1.4	Lap.....	8-3	10.1.1.2.1	Mismatch.....	10-6
8.1.4.1	Two or More Conductors	8-4	10.1.1.2.2	Fit.....	10-7
8.1.5	Heat Shrinkable Solder Devices.....	8-6	10.1.1.2.3	Cracks, Flow Lines, Chill Marks (Knit Lines) or Weld Lines.....	10-9
8.2	Crimped Splices	8-8	10.1.1.2.4	Color.....	10-11
8.2.1	Barrel.....	8-8	10.1.2	Blow Through	10-11
8.2.2	Double Sided	8-10	10.1.3	Position	10-12
8.2.3	Contact.....	8-12	10.1.4	Flashing.....	10-15
8.2.4	Wire In-Line Junction Devices	8-13	10.1.5	Wire Insulation, Jacket or Sleeving Damage ..	10-17
8.3	Ultrasonic Weld Splices	8-14	10.2	Potting (Thermoset Molding)	10-18
8.4	Sleeving Over Splices	8-14	10.2.1	Filling.....	10-18
9.0	CONNECTORIZATION	9-1	10.2.2	Fit to Wire or Cable.....	10-21
9.1	Hardware Mounting	9-1	10.2.3	Curing	10-22
9.1.1	Jackpost – Height.....	9-1	10.3	Over-Molding of Flexible Flat Ribbon	10-23
9.1.2	Jackscrews – Protrusion.....	9-2	10.3.1	Mounting and Alignment Feature Adhesion... ..	10-25
9.1.3	Retaining Clips	9-3	10.3.2	Adhesion Between Ribbon and Connector Potting	10-25
9.1.4	Connector Alignment	9-4	10.3.3	Mounting Hardware	10-26
9.2	Strain Relief	9-5			
9.2.1	Clamp Fit	9-5			

Table of Contents (cont.)

11.0	MEASURING CABLE ASSEMBLIES AND WIRES	11-1	13.7.2	Press Fit	13-13
11.1	Cable and Wire Length Tolerance	11-1	13.8	Shield Termination	13-13
11.2	Cable	11-1	13.8.1	Clamped Ground Rings	13-13
11.2.1	Straight/Axial Connectors	11-1	13.8.2	Crimped Ferrule	13-14
11.2.2	Right-Angle Connectors	11-1	13.9	Center Pin	13-16
11.2.3	Length	11-2	13.9.1	Position	13-16
11.2.4	Breakout	11-2	13.9.2	Damage	13-17
11.2.4.1	Breakout Measurement Points	11-2	13.10	Semirigid Coax	13-17
11.2.4.2	Breakout Length	11-3	13.10.1	Bending and Deformation	13-18
11.3	Wire	11-3	13.10.2	Surface Condition	13-20
11.3.1	Electrical Terminal Reference Location	11-3	13.10.2.1	Solid	13-20
11.3.2	Length	11-4	13.10.2.2	Conformable Cable	13-21
12.0	MARKING/LABELING	12-1	13.10.3	Dielectric Cutoff	13-22
12.1	Content	12-1	13.10.4	Dielectric Cleanliness	13-24
12.2	Legibility	12-2	13.10.5	Center Conductor Pin	13-24
12.3	Permanency	12-3	13.10.5.1	Damage	13-25
12.4	Location and Orientation	12-4	13.10.6	Solder	13-25
12.5	Direct Marking	12-5	13.11	Swage-Type Connector	13-27
12.6	Marker Sleeve	12-6	13.12	Soldering and Stripping of Biaxial/Multi-Axial Shielded Wire	13-28
12.6.1	Wrap Around	12-6	13.12.1	Jacket and Tip Installation	13-28
12.6.2	Tubular	12-7	13.12.2	Ring Installation	13-30
12.7	Flag Markers	12-7	14.0	SECURING	14-1
12.7.1	Adhesive	12-7	14.1	Restraining Device Application	14-1
12.8	Tie Wrap Markers	12-8	14.1.1	Tightness	14-6
13.0	COAXIAL AND BIAxIAL CABLE ASSEMBLIES	13-1	14.1.2	Damage	14-7
13.1	Stripping	13-1	14.1.3	Spacing	14-8
13.2	Center Conductor Termination	13-4	14.2	Breakouts	14-8
13.2.1	Crimp	13-4	14.2.1	Individual Wires	14-8
13.2.2	Solder	13-5	14.2.2	Spacing	14-9
13.3	Solder Ferrule Pins	13-6	14.3	Routing	14-12
13.3.1	General	13-6	14.3.1	Wire Crossover	14-12
13.3.2	Insulation	13-7	14.3.2	Bend Radius	14-13
13.4	Printed Wire Board Mount	13-8	14.3.3	Coaxial Cable	14-14
13.5	Right Angle Connector	13-9	14.3.4	Unused Wire Termination	14-15
13.6	Center Conductor Solder	13-10	14.3.4.1	Shrink Sleeving	14-15
13.7	Terminal Cover	13-12	14.3.4.2	Flexible Sleeving	14-16
13.7.1	Soldering	13-12	14.3.5	Restraining Device over Splices and Ferrules	14-16

Table of Contents (cont.)

14.4	Broom Stitching	14-17	16.5	Tapes, Adhesive and Non-Adhesive	16-8
15.0	HARNESS/CABLE ELECTRICAL SHIELDING	15-1	17.0	FINISHED ASSEMBLY INSTALLATION	17-1
15.1	Braided	15-1	17.1	General	17-1
15.1.1	Direct Applied	15-2	17.2	Hardware Installation	17-3
15.1.2	Prewoven	15-3	17.2.1	Threaded Fasteners	17-4
15.2	Shield Termination	15-4	17.2.1.1	Minimum Torque	17-6
15.2.1	Shield Jumper Wire	15-4	17.2.2	Wires	17-8
15.2.1.1	Attached Lead	15-4	17.2.2.1	Solid Wires	17-8
15.2.1.1.1	Solder	15-4	17.2.2.2	Stranded Wires	17-10
15.2.1.1.2	Crimp	15-7	17.2.3	Safety Wiring	17-11
15.2.1.2	Shield Braid	15-8	17.2.4	Safety Cable	17-13
15.2.1.2.1	Woven	15-8	17.3	Wire/Harness Installation	17-14
15.2.1.2.2	Combed and Twisted	15-8	17.3.1	Stress Relief	17-14
15.2.1.3	Daisy Chain	15-9	17.3.2	Wire Dress	17-15
15.2.1.4	Common Ground Point	15-10	17.3.3	Service Loops	17-16
15.2.2	Unterminated Shield	15-10	17.3.4	Clamping	17-16
15.2.2.1	Shield Not Folded Back	15-11	17.3.5	Restraining Devices	17-17
15.2.2.2	Shield Folded Back	15-11	17.3.6	Raceways	17-17
15.3	Connector	15-12	17.3.7	Grommets	17-19
15.3.1	Shrink	15-12	17.3.7.1	Sealing Not Required	17-19
15.3.2	Crimp	15-13	17.3.7.2	Sealing Required	17-20
15.3.3	Shield Jumper Wire Attachment	15-15	18.0	SOLDERLESS WRAP	18-1
15.3.4	Soldered	15-16	19.0	TESTING	19-1
15.4	Splicing Prewoven	15-16	19.1	Nondestructive Tests	19-1
15.4.1	Soldered	15-17	19.2	Testing After Rework or Repair	19-1
15.4.2	Tie/Tape On	15-18	19.3	Electrical Test	19-1
15.5	Tapes – Barrier and Conductive, Adhesive or Non-Adhesive	15-19	19.3.1	Electrical Test Methods	19-1
15.6	Conduit (Shielding)	15-20	19.3.1.1	Continuity	19-1
15.7	Shrink Tubing – Conductive Lined	15-20	19.3.1.2	Shorts	19-2
16.0	CABLE/WIRE HARNESS PROTECTIVE COVERINGS	16-1	19.3.1.3	Dielectric Withstanding Voltage (DWV)	19-2
16.1	Braid	16-1	19.3.1.4	Insulation Resistance (IR)	19-3
16.1.1	Direct Applied	16-1	19.3.1.5	Voltage Standing Wave Ratio (VSWR)	19-4
16.1.2	Prewoven	16-3	19.3.1.6	Insertion Loss	19-4
16.2	Sleeving/Shrink Tubing	16-5	19.3.1.7	Reflection Coefficient	19-4
16.2.1	Sealant	16-6	19.4	Mechanical Test	19-5
16.3	Spiral Plastic Wrap (Spiral Wrap Sleeving)	16-7	19.4.1	Mechanical Test Methods	19-5
16.4	Wire Loom Tubing – Split and Unsplit	16-8	19.4.1.1	Crimp Height	19-5
			19.4.1.2	Pull Force (Tensile)	19-6
			19.4.1.3	Contact Retention Verification	19-8

Table of Contents (cont.)

19.4.1.4	RF Connector Shield Pull Force (Tensile).....	19-8	Table 19-2	Shorts (Low Voltage Isolation) Test Minimum Requirements	19-2
19.4.1.5	RF Connector Shield Ferrule Torsion.....	19-8	Table 19-3	Dielectric Withstanding Voltage (DWV) Test Minimum Requirements	19-2
20.0	HIGH VOLTAGE APPLICATIONS	20-1	Table 19-4	Insulation Resistance (IR) Test Minimum Requirements	19-3
Appendix A	Terms and Definitions	A-1	Table 19-5	Voltage Standing Wave Ratio (VSWR) Test Parameters	19-4
Appendix B	Reproducible Test Tables	B-1	Table 19-6	Insertion Loss Test Parameters	19-4
Appendix C	Guidelines for Soldering Tools and Equipment	C-1	Table 19-7	Reflection Coefficient Test Parameters	19-4
Appendix D	X-Ray Guidelines	D-1	Table 19-8	Pull Test Force Values	19-7
			Table 19-9	RF Connector Shield Pull Force Testing.....	19-8
			Table A-1	Electrical Clearance	A-2
			Table 19-1	Continuity Test Minimum Requirements	B-2
			Table 19-2	Shorts (Low Voltage Isolation) Test Minimum Requirements	B-3
			Table 19-3	Dielectric Withstanding Voltage (DWV) Test Minimum Requirements	B-4
			Table 19-4	Insulation Resistance (IR) Test Minimum Requirements	B-5
			Table 19-5	Voltage Standing Wave Ratio (VSWR) Test Parameters	B-6
			Table 19-6	Insertion Loss Test Parameters	B-7
			Table 19-7	Reflection Coefficient Test Parameters	B-8
			Table 19-9	RF Connector Shield Pull Force Testing.....	B-9
Tables					
Table 1-1	Magnification Aid Applications – Wire and Wire Connections	1-5			
Table 1-2	Magnification Aid Applications – Other	1-6			
Table 3-1	Allowable Strand Damage	3-2			
Table 4-1	Maximum Limits of Solder Bath Contaminant	4-2			
Table 4-2	Solder Connection Anomalies.....	4-8			
Table 4-3	Turret or Straight Pin Terminal Lead/ Conductor(s) Placement	4-20			
Table 4-4	Bifurcated Terminal Lead/Conductor(s) Placement – Side Route.....	4-23			
Table 4-5	Bifurcated Terminal Lead/Conductor(s) Placement – Bottom Route.....	4-25			
Table 4-6	Staking Requirements of Side Route Straight Through Connections – Bifurcated Terminals	4-26			
Table 4-7	Pierced/Perforated/Punched Terminal Lead/Conductor(s) Placement.....	4-31			
Table 4-8	Hook Terminal Lead/Conductor(s) Placement.....	4-33			
Table 4-9	AWG 30 and Smaller Wire Wrap Requirements.....	4-39			
Table 11-1	Cable/Wire Length Measurement Tolerance ..	11-1			
Table 13-1	Coaxial and Biaxial Shield and Center Conductor Damage	13-1			
Table 13-2	Semirigid Coax Deformation	13-19			
Table 13-3	Dielectric Cutoff	13-22			
Table 14-1	Minimum Bend Radius Requirements	14-13			
Table 15-1	Braid Damage	15-3			
Table 17-1	Minimum Swaged Ferrule Pull-Off Load....	17-13			
Table 19-1	Continuity Test Minimum Requirements	19-1			

1.0 GENERAL

1.1 Scope This standard prescribes practices and requirements for the manufacture of cable, wire and harness assemblies. This standard does not provide criteria for cross-section or X-ray evaluation. For X-ray guidelines, see Appendix D X-Ray Guidelines.

If a conflict occurs between the English and translated versions of this document, the English version will take precedence.

The illustrations in this document portray specific points noted in the title of each section. The development committee recognizes that different parts of the industry have different definitions for some terms used herein. For the purposes of this document, the terms cable and wire harness are used interchangeably.

IPC/WHMA-A-620 can be used as a stand-alone document for purchasing products, however it does not specify frequency of in-process inspection or frequency of end product inspection. No limit is placed on the number of process indicators or the number of allowable repair/rework of defects. Such information should be developed with a statistical process control plan (see IPC-9191).

1.2 Purpose This standard describes materials, methods, tests and acceptability criteria for producing crimped, mechanically secured, or soldered interconnections and the related assembly activities associated with cable and wire harness assemblies.

The intent of this document is to rely on process control methodology to ensure consistent quality levels during the manufacture of products.

It is acceptable to use any method that produces an assembly conforming to the acceptability requirements described in this standard.

Standards may be updated at any time, including with the use of amendments. The use of an amendment or newer revision is not automatically required. The revision in effect **shall [D1D2D3]** be as specified by the User.

1.3 Classification Use of this standard requires agreement on the Class to which the product belongs. The User has the ultimate responsibility for identifying the Class to which the assembly is evaluated. If the User does not establish and document the acceptance Class, the Manufacturer may do so. Criteria defined in this standard reflect three Product Classes, which are as follows:

Class 1 General Electronic Products

Includes products suitable for applications where the major requirement is the function of the completed assembly.

Class 2 Dedicated Service Electronic Products

Includes products where continued performance and extended life is required, and for which uninterrupted service is desired but not critical. Typically, the end-use environment would not cause failures.

Class 3 High Performance/Harsh Environment Electronic Products

Includes products where continued performance or performance-on-demand is critical, equipment downtime cannot be tolerated, end-use environment may be uncommonly harsh, and the equipment must function when required, such as life support systems and other critical systems.

1.4 Measurement Units and Applications This document uses the International System of Units (SI) in accordance with IEEE/ASTM SI 10, American National Standard for Metric Practice (Section 3). Imperial English equivalent units follow in brackets. The derived SI units used in this document are millimeters (mm) [in] for dimensions and dimensional tolerances, Celsius (°C) [°F] for temperature and temperature tolerances, grams (g) [oz] for weight, and lux (lx) [foot-candles] for illuminance. Conductor sizes are expressed in American Wire Gauge (AWG).

1.4.1 Verification of Dimensions Where not specifically invoked by this standard, actual measurements, e.g., of specific solder fillet dimensions, determination of damage and wrap percentages, are not required except for referee purposes.

1.4.2 Relationship of AWG and Wire Size AWG numbers increase as the conductor diameter decreases. For example, 22 AWG has a conductor with a smaller diameter than 11 AWG. In this standard, when “smaller than” or “larger than” is used in reference to wire size, it is referencing the wire diameter and not the wire gauge.

1.5 Definition of Requirements The words “**shall**” or “**shall not**” are used in the text of this document wherever there is a requirement for materials, process or acceptance of cable and wire harness assemblies.

Where the words “**shall**” or “**shall not**” indicates a requirement for at least one Class, the requirements for each Class are in brackets next to the “**shall**” or “**shall not**” requirement.